

Sharp Signage Display

MultiSync ME432



For exceptional performance in meetings rooms and digital signage solutions, the ME-series offers best-in-class visual performance and value to support your range of needs.

- Seamless connectivity – native USB-C supports Bring Your Own Device workflows, safeguarding inclusion and boosting productivity, with a single cable connection between notebook and display.
- Best readability – aiding high productivity in well-lit meeting spaces, a high haze filter eliminates glare and reflections from windows and other light sources.
- Quick input detection – removing potential frustration and smoothing the way to productive meeting outcomes, the display responds immediately when a device is connected.
- Third-party compatibility – not simply a display, but an out-of-the-box solution, compatible with popular workplace and content management systems through the integrated SoC platform.
- New feature-ready – regular OTA Android OS updates ensure availability of the latest features and system security.

Specificaties

Accessoires

[AVSpecificationAccessories]	Zender Afstandsbediening, Installatie Set-Up Handleiding, Netsnoer, HDMI-kabel, Bevestigingsbeugel, Tafelstandaard, Trolley Standaard, Batterij
Shipping Content	2x AAA-batterijen, Weergave, HDMI-kabel, Stroomkabel, Afstandsbediening, Installatiehandleiding
Special Characteristics	Frame Comp, Actieve USB-poort (10 W), Actieve USB-poort (5 W), Actieve USB-poort (15 W)
Beperkte fabrieksgarantie (jaren.)	3
Ingebouwde luidsprekers (W)	10 + 10
Energiebeheer	True
Ruimte Apparatuur (Montage)	True
Kleur Behuizing	Zwart
Planner / Timer	True
Liggend	True
Staand	True
Bevestiging (VESA/Aantal Punten/Pitch mm)	200 x 200 (FDMI)
Bevestiging (VESA/Aantal Punten/Pitch mm)	4
Bevestigingsbout Specificatie (grootte/Max Lengte)	M6
RS232C IN	1
LAN-poort	1
USB	4
Beelddiagonaal (inches / cm)	43
Beelddiagonaal (inches / cm)	108
Grootte Omlijsting (L/R) mm	10
Grootte Omlijsting (U) mm	10
Haze Level [%]	Pro 25

Panel Technologie	IPS with Direct LED backlights
Eigen resolutie (aantal pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technologie	LED
Helderheid (cd/m2)	400
Contrast Ratio	1200:1
Reactietijd (grijs naar grijs gem) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (8bit + FRC)

Bedrijfsspanning (ACV) / Frequentie (Hz)	100-240
Bedrijfsspanning (ACV) / Frequentie (Hz)	50-60
Stroomverbruik (W) (MAX)	90
Werkende Temperatuur (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	90

Afmetingen Verpakkingsdoos (B/H/D) mm	1056
Afmetingen Verpakkingsdoos (B/H/D) mm	632
Afmetingen Verpakkingsdoos (B/H/D) mm	156
Gewicht zonder standaard (kg)	9
Transportgewicht (Kg)	14

HDMI	0
[AVSpecificationConnectivityOutputAudio35MmJack]	1
Audio/Koptelefoon Aansluiting 3,5 mm	1

HDMI	3
Audio-aansluiting van 3,5 mm	1

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Energie Sterren	True
-----------------	------