

Sharp Signage Display

Sharp MultiSync® E329 LCD 32" Essential Large Format Display



Professional performance, affordable value

- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Standardised functionality – shares a common identity with the wider Sharp display portfolio, ensuring unified operation and remote device management, and consistent styling for a seamless user experience.
- Effortless plug-and-play signage – the integrated USB MediaPlayer enables native UHD content playback with auto-start functionality, delivering instant digital signage without the need for external hardware or content management systems.
- Flexible orientation – designed for both portrait and landscape installation, with uniform bezel width on all sides to ensure a clean, professional look in any configuration.

Specifications

Video Terminals

Control Terminals	RS232C
-------------------	--------

Key Specifications

Special Characteristics	NaViSet Administrator 2, CEC Support, USB Media Player, Powered USB-Port, HDMI ARC, Scheduler
Built in Speakers (W)	5 + 5
Remote Management	True
Operating Time	16/7
Supported Image Format	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)

Resolution

Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1920 x 1200, 1024 x 768 , 1280 x 1024, 1920 x 1080, 640 x 480, 1280 x 720, 1280 x 960, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1400 x 1050, 1280 x 800, 4096 x 2160

Accessories

Accessories	Feet, Trolley, USB-C cable, Wall mount
Shipping Content	Setup Manual, 2 x AAA batteries, Remote Control, Cable Clamps, Display, Power Cable

Installation

Landscape	True
Portrait	True
Mounting (VESA mm)	200 x 200 (FDMI)
Mounting (Number of Points/Pitch)	4
Mounting Screw Specification (Size/Max Length)	M6

Mechanical

Bezel Width (Left/Right) [mm]	11
Bezel Width (Upper) [mm]	11
Bezel Width (Lower) [mm]	11

Display

Screen Size (inch)	32
Screen Size (cm)	80

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 75

Environmental Conditions

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Display Module Data

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	1920 x 1080
Aspect Ratio	16:9
Brightness (cd/m ²)	350
Contrast Ratio	1200:1
Pixel Pitch (mm)	0.364
Viewing Angle (°)	178
Colour Depth [bn]	16.7 (8bit)
Active Screen Area (H/V) mm	698 x 393
Response Time (typ.) [ms]	8

Power Supply and Operating Environment

Operating Voltage (ACV)	100-240
Frequency (Hz)	50-60
Via AC Adapter	True
Operating Temperature (°C)	0 - 40
Storage Temperature (°C)	-20 - 60
Storage Humidity Min [%]	10
Storage Humidity Max [%]	80
Power Saving Mode (W)	< 2 (Networked Standby)

Additional Features

Colour Versions	Black Front Bezel, Black Back Cabinet
Safety and Ergonomics	UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM
Warranty	3 years warranty incl. backlight

Weights and Measures

Shipping Carton Dimensions (Width) mm	824
Shipping Carton Dimensions (Height) mm	554
Shipping Carton Dimensions (Depth) mm	119
Product Weight Without Stand (Kg)	5
Shipping Weight (Kg)	7

Green Features

Energy Efficiency	Energy Consumption: 44kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	Energy Star 8.0

Ergonomics

Landscape Dimensions (Width) [mm]	724
Landscape Dimensions (Height) [mm]	418
Landscape Dimensions (Depth) [mm]	59

Connectivity

Digital	HDMI, USB Type C
Output Control	LAN 100Mbit

Touch Interface Specification

Haze Level [%]	Standard 25
----------------	-------------

Electrical

Power Consumption on Mode [W]	43 (shipping)
-------------------------------	---------------



NaViSet
Administrator 2



USB Type-C®

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® E329 LCD 32" Essential Large Format Display, 15/7/2026