

8k Display

8M-B32C1



Een 32 inch 8K LCD display voor professioneel gebruik. Perfect voor ontwerp- en fotostudio's, medische documenten, uitzendingen, controlekamers, bewakingsbeelden, wetenschap, CAD en meer.

- 32 (80 cm) diagonaal LCD (IGZO)
- Native 8K 7680 x 4320 pixelresolutie
- High Dynamic Range (HDR) (HLG/PQ)
- 10-Bit uitgebreid kleurengamma
- Helderheid 800 cd/m² (Peak 1.000 cd/m²)
- Direct LED backlight met local dimming
- Uniformiteitscorrectie, SHARP Advanced UCCT
- Hardware kalibratie, SHARP Display Calibration Utility

Specificaties

Panel Technologie	LCD (IGZO)
Eigen resolutie (aantal pixels)	7680 x 4320
Aspect Ratio	16:9
Backlight Technologie	Direct LED
Helderheid (cd/m2)	800
Contrast Ratio	1000000:1
Kleuren Display	1064.64
Reactietijd (grijs naar grijs gem) ms	9
Pixel Pitch (mm H/V)	0,091
Pixels Per Inch (ppi)	280
Afmetingen Verpakkingsdoos (B/H/D) mm	861
Afmetingen Verpakkingsdoos (B/H/D) mm	636
Afmetingen Verpakkingsdoos (B/H/D) mm	375
Gewicht zonder standaard (kg)	13
Gewicht met standaard (kg)	192
Transportgewicht (Kg)	23
Liggend	True
Staand	True
Bevestiging (VESA/Aantal Punten/Pitch mm)	200 x 200
Bevestigingsbout Specificatie (grootte/Max Lengte)	M6
Grootte Omlijsting (L/R) mm	26
Grootte Omlijsting (U) mm	26
Grootte Omlijsting (L) mm	49
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationConnectivityOutputAudio35MmJack]1	
[AVSpecificationTechnology]	No

HDR High Dynamic Range	HLG, PQ
Beperkte fabrieksgarantie (jaren.)	3
Lokaal Dimmen	True
Computer Input - Plug en Play	True
Kleur Behuizing	Zwart
Ventilatorregeling	Auto, Manual
Temperatuur Sensor	True
Multi Talen OSD	True
Beheer Afstandsbediening	True
Versterkingsregeling	True
Scherf Aanpassen	True
Kleur Temeperatuur Aanpassing	True
Gammabeheer	True
Automatisch Aanpassen	True
Temperatuurregeling	True
RS232C Communicatie Snelheid Wijzigen	True
Bedrijfsspanning (ACV) / Frequentie (Hz)	100-240
Bedrijfsspanning (ACV) / Frequentie (Hz)	50-60
Stroomverbruik (W) (MAX)	260
Stroomverbruik (W) (Stand-by)	0,5
Werkende Temperatuur (oC)	0 - 35
Beelddiagonaal (inches / cm)	32
Beelddiagonaal (inches / cm)	80
Colour Gamuts	85% BT2020, 100 % sRGB, 96% DCI-P3
DisplayPort	1
HDMI	6
CE, CB Rapport	True
USB	2



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: 8M-B32C1, 14/7/2026