

Desktopdisplays

Sharp/ NEC MultiSync EA271Q



NEC MultiSync

- Op het scherm zijn meer details te zien - de Quad HD-resolutie van maximaal 2560×1440 pixels biedt 1,75 keer meer schermdetails in vergelijking met Full HD.
- Nieuwste connectiviteitsstandaard USB-C - optimale connectiviteit en een opgeruimde werkplek: vervang video-, audio-, stroom- en USB-kabels door slechts één enkele kabel.
- Maximale aandacht voor de gezondheid en het welzijn van de gebruiker - met uitstekende ergonomische hoogteverstelling tussen 0 en 150 mm; ingebouwde Low Blue Light- en Flicker-Free-technologie; plus g
- Het gemak van meerdere schermen - met de ControlSync®-technologie beheer je de instellingen van maximaal 8 schermen in een configuratie met meerdere monitoren via het hoofdscherm.
- Uitstekende vorm en functionaliteit - toekomstgericht ontwerp met 3-zijdige, dunne behuizing, leverbaar in zwart of wit voor een even fris als professioneel ogend kantoorinterieur.

Specificaties

Panel Technologie	IPS TFT with W-LED backlight
Aspect Ratio	16:9
Helderheid (cd/m2)	350
Contrast Ratio	1000:1
[AVSpecificationDynamicContrastRatio]	7000:1
Kleuren Display	16.78
Reactietijd (grijs naar grijs gem) ms	6
Pixel Pitch (mm H/V)	0,233
Viewing Angle [°]	178
Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	362
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	629
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Energy Efficiency	Ambient light sensor, ECOMode, Energy consumption: 21 kWh/1000 h, Energy efficiency class: E, Human sensor
Ecological Standards	Minimaal gebruik van schadelijk materiaal
Ecological Materials	Energy Star 8.0, Voldoet aan ErP, Voldoet aan RoHS, TCO 8.0, [tco-edge]
Optimum Resolution	2560 x 1440 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1152 x 864, 1600 x 1200, 1920 x 1080, 1920 x 1440, 2560 x 1440, 640 x 480, 800 x 600, 832 x 624
Werkende Temperatuur (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Accessoires	
Shipping Content	Control Sync-kabel, DisplayPoort-kabel, Monitor, Stroomkabel, Installatiegids, USB-kabel
Bevestiging (VESA/Aantal Punten/Pitch mm)	100 x 100
Kensington-slot	True
Horizontal Frequency [kHz]	31.5 - 94
Vertical Frequency [Hz]	50 - 75
Grootte Omlijsting (L/R) mm	1
Grootte Omlijsting (U) mm	1

Colour Versions	Zwarte voorkant, Zwarte achterkant, Witte voorkant, Witte achterkant
Cable Management Plug & Play	True DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	1W + 1W (uitschakelbaar), Koptelefoonaansluiting
Adjust Functions	Audiovolume / vergrendeling, Automatische aanpassing, Helderheid, Kleurtemperatuurregeling, Contrast, Control Sync, DV-modus, Eco-modus, Aanwezigheidssensor, Intelligent stroombeheer, Taalkeuze, Monitorinformatie, OSD-vergrendeling (On-Screen-Display, beeldschermdisplay), One Touch Recovery, Uitschakeltimer
Safety & Ergonomics	CE, EAC, ErP, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 8.0, TCO Edge Certified 1.2, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Beperkte fabrieksgarantie (jaren.)	3 jaar garantie incl. achtergrondverlichting, Optioneel 1e tot 3e jaar 24/7 gebruiksgarantie, Optionele verlenging van de garantie van 4 tot 5 jaar
Special Characteristics	DDC/CI compatible, RGB Support, Frame Comp, PJLink-ondersteuning, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Aanraaktoetsen, USB versie 3.0 (3 omlaag / 1 omhoog), Niet-flikkerend
Stroomverbruik aan-modus (IEC62087:2012)	150 (max.), 30 (Eco Mode 2), 37 (Eco Mode 1), 37 (shipping), 37 (typ.)
Power Supply	0.75 A/1.6 A, 100-240 V, Internal Power Supply
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (3 down / 1 up), USB Type C (60 W), DVI-D (Dual Link)
Beelddiagonaal (inches / cm)	27
Beelddiagonaal (inches / cm)	68
Colour Gamuts	100 % sRGB, 75 % NTSC
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Gewicht met standaard (kg)	9



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp/ NEC MultiSync EA271Q, 14/7/2026