

Sharp Signage Display

Sharp MultiSync® E439




Professionele prestaties, betaalbare prijs.

- Onbelemmerde leesbaarheid – een paneel met een hoge waas vermindert reflecties van ramen en omgevingslicht, waardoor de inhoud van bewegwijzering en presentaties helder en ongestoord leesbaar blijven, ongeacht de omgeving.
- Gestandaardiseerde functionaliteit – deelt een gemeenschappelijke identiteit met de rest van het Sharp-schermportfolio, wat zorgt voor uniforme bediening en beheer op afstand, en een consistente vormgeving voor een naadloze gebruikerservaring.
- Eenvoudige plug-and-play signage – de geïntegreerde USB-mediaspeler maakt het mogelijk om native UHD-content af te spelen met automatische startfunctie, waardoor direct digitale signage beschikbaar is zonder dat externe hardware of contentmanagementsystemen nodig zijn.
- Flexibele oriëntatie – ontworpen voor zowel verticale als horizontale installatie, met een uniforme randbreedte aan alle zijden voor een strakke, professionele uitstraling in elke configuratie.

Specificaties

[AVSpecificationControlTerminals]	RS232C
Special Characteristics	NaViSet Administrator 2, CEC-ondersteuning, USB-mediaspeler, USB-poort, HDMI ARC, Planner 10 + 10
Ingebouwde luidsprekers (W)	True
Beheer Afstandsbediening	16/7
Operating Time	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)
[AVSpecificationSupportedImageFormats]	
Colour Versions	Zwarte voorkant, Zwarte achterkant
Safety & Ergonomics	UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM
Beperkte fabrieksgarantie (jaren.)	3 jaar garantie incl. achtergrondverlichting
Accessoires	
[AVSpecificationAccessories]	[feet], [trolley], [usb-c-cable], [wall-mount]
Shipping Content	Installatiehandleiding, 2x AAA-batterijen, Afstandsbediening, Cable Clamps, Weergave, Stroomkabel
Liggend	True
Staand	True
Bevestiging (VESA/Aantal Punten/Pitch mm)	200 x 200 (FDMI)
Bevestiging (VESA/Aantal Punten/Pitch mm)	4
Bevestigingsbout Specificatie (grootte/Max Lengte)	M6
Grootte Omlijsting (L/R) mm	11
Grootte Omlijsting (U) mm	11
Grootte Omlijsting (L) mm	11
[AVSpecificationLandscapeDimensionsWidthMm]	965
[AVSpecificationLandscapeDimensionsHeightMm]	555
[AVSpecificationLandscapeDimensionsDepthMm]	60
Digital	HDMI, USB Type C
Output Control	LAN 100Mbit
Haze Level [%]	Pro 25
Stroomverbruik aan-modus (IEC62087:2012)	85 (shipping)

Panel Technologie	IPS with Direct LED backlights
Eigen resolutie (aantal pixels)	3840 x 2160
Aspect Ratio	16:9
Helderheid (cd/m2)	350
Contrast Ratio	1200:1
Pixel Pitch (mm H/V)	0,245
Viewing Angle [°]	178
Colour Depth [bn]	1.07 (8bit + FRC)
Actief schermoppervlak (H / V) mm	941 x 529
Response Time (typ.) [ms]	8
Bedrijfsspanning (ACV) / Frequentie (Hz)	100-240
Bedrijfsspanning (ACV) / Frequentie (Hz)	50-60
Via AC-Adapter	True
Werkende Temperatuur (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
Supported Resolution	1920 x 1200, 1024 x 768, 1280 x 1024, 1920 x 1080, 640 x 480, 1280 x 720, 1280 x 960, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1400 x 1050, 1280 x 800, 4096 x 2160
Afmetingen Verpakkingsdoos (B/H/D) mm	1075
Afmetingen Verpakkingsdoos (B/H/D) mm	683
Afmetingen Verpakkingsdoos (B/H/D) mm	127
Gewicht zonder standaard (kg)	8
Transportgewicht (Kg)	11
Energy Efficiency	Energy Consumption: 82kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	Energy Star 8.0
Beelddiagonaal (inches / cm)	43
Beelddiagonaal (inches / cm)	108
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® E439, 15/7/2026