

Sharp Signage Display

Sharp MultiSync® M862




Gebouwd voor optimale prestaties, ontworpen voor een lange levensduur.

- Naadloze vergaderworkflows – één enkele USB-C-kabel verzendt video, data en stroom voor een snelle en overzichtelijke opzet van vergaderingen, en USB-C ondersteunt een probleemloze BYOD-ervaring.
- Onbelemmerde leesbaarheid – een paneel met een hoge haze vermindert reflecties van ramen en omgevingslicht, waardoor de inhoud van de borden en presentaties helder en ongestoord leesbaar blijven in elke omgeving.
- Beveiliging gegarandeerd – 802.2x-ondersteuning via LAN zorgt voor een hoog beveiligingsniveau voor bedrijfsnetwerken, wat IT-teams en bedrijfsomgevingen gemoedsrust biedt.
- Verbeterde beeldprecisie – wanneer merkconsistentie en huisstijl belangrijk zijn, biedt Sharp's SpectraView Engine volledige controle over kleur, gamma en uniformiteit voor nauwkeurige en impactvolle content.
- Brede AV-compatibiliteit – volledig interoperabel met toonaangevende vergaderruimteplatformen zoals Crestron (XiO Cloud), Cisco Webex, Q-Sys en Microsoft Teams, wat een moeiteloze integratie garandeert.

Specificaties

[AVSpecificationControlTerminals]	RS232C
Special Characteristics	CEC-ondersteuning, HDMI ARC, Planner, DICOM-simulatie, [clone-settings]
24/7 Werking Gecertificeerd	True
Ingebouwde luidsprekers (W)	10 + 10
Energiebeheer	True
Temperatuur Sensor	True
Beheer Afstandsbediening	True
Operating Time	24/7
Frame Material	Metal
Accessoires	
[AVSpecificationAccessories]	[eco-sensor], [feet], [remote-control-kit], [speaker], [trolley], [usb-c-cable], [wall-mount]
Shipping Content	Installatiehandleiding, 2x AAA-batterijen, HDMI-kabel, Afstandsbediening, Weergave, Stroomkabel
Bedrijfsspanning (ACV) / Frequentie (Hz)	100-240
Bedrijfsspanning (ACV) / Frequentie (Hz)	50-60
Via AC-Adapter	True
Werkende Temperatuur (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
Afmetingen Verpakkingsdoos (B/H/D) mm	2090
Afmetingen Verpakkingsdoos (B/H/D) mm	1225
Afmetingen Verpakkingsdoos (B/H/D) mm	225
Gewicht zonder standaard (kg)	47
Transportgewicht (Kg)	64
Beelddiagonaal (inches / cm)	86
Beelddiagonaal (inches / cm)	217
Colour Gamuts	72% NTSC
Digital	DisplayPort, DisplayPort out, USB Type C
Output Control	LAN 100Mbit
[AVSpecificationLandscapeDimensionsWidthMm]	1928
[AVSpecificationLandscapeDimensionsHeightMm]	1099
[AVSpecificationLandscapeDimensionsDepthMm]	83
Ingebouwde luidsprekers (W)	Internal 10W + 10W
Haze Level [%]	Pro 25

Colour Versions	Zwarte voorkant, Zwarte achterkant
Safety & Ergonomics	EMC Class B, UKCA, ISO 9241-307 (pixel failure class I), RoHS, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, REACH
Beperkte fabrieksgarantie (jaren.)	3 jaar garantie incl. achtergrondverlichting, Optionele verlenging van de garantie van 4 tot 5 jaar, [additional-services-available]
Supported Resolution	1270 x 720, 1920 x 2160, 1920 x 1200, 1024 x 768, 1280 x 1024, 1600 x 1200, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 720, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1366 x 768, 1400 x 1050, 1280 x 800, 4096 x 2160
Panel Technologie	IPS with Direct LED backlights
Eigen resolutie (aantal pixels)	3840 x 2160
Aspect Ratio	16:9
Helderheid (cd/m2)	550
Contrast Ratio	8000:1
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Response Time (typ.) [ms]	8
Liggend	True
Staand	True
Bevestiging (VESA/Aantal Punten/Pitch mm)	600 x 400 (FDMI)
Bevestiging (VESA/Aantal Punten/Pitch mm)	4
Bevestigingsbout Specificatie (grootte/Max Lengte)	M8
[AVSpecificationFaceUp]	True
Energy Efficiency	Energy Consumption: 189kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	Energy Star 8.0
Grootte Omlijsting (L/R) mm	14
Grootte Omlijsting (U) mm	14
Grootte Omlijsting (L) mm	15
Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Stroomverbruik aan-modus (IEC62087:2012)	190 (shipping)



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® M862, 14/7/2026