Sharp Signage display

MultiSync ME552



Voor uitzonderlijke prestaties in vergaderruimtes en digitale signage-oplossingen biedt de ME-serie de beste visuele prestaties en waarde ter ondersteuning van al uw behoeften.

- Seamless connectivity – native USB-C supports Bring Your Own Device workflows, safeguarding inclusion and boosting productivity, with a single cable connection between notebook and display.
- Best readability – aiding high productivity in well-lit meeting spaces, a high haze filter eliminates glare and reflections from windows and other light sources.
- Quick input detection – removing potential frustration and smoothing the way to productive meeting outcomes, the display responds immediately when a device is connected.
- Third-party compatibility – not simply a display, but an out-of-the-box solution, compatible with popular workplace and content management systems through the integrated SoC platform.
- New feature-ready – regular OTA Android OS updates ensure availability of the latest features and system security.

Specificaties

Accessoires

[AVSpecificationAccessories]	Zender Afstandsbediening, Installatie Set-Up Handleiding, Netsnoer, HDMI-kabel, Bevestigingsbeugel, Tafelstandaard, Trolley Standaard, Batterij
Shipping Content	2× AAA-batterijen, Weergave, HDMI-kabel, Stroomkabel, Afstandsbediening, Installatiehandleiding
Special Characteristics	Frame Comp, Actieve USB-poort (10 W), Actieve USB-poort (5 W), Actieve USB-poort (15 W)
Beperkte fabrieksgarantie (jaren.)	3
Ingebouwde luidsprekers (W)	10 + 10
Energiebeheer	Ja
Ruimte Apparatuur (Montage)	Ja
Kleur Behuizing	Zwart
Planner / Timer	Ja
Afmetingen Verpakkingsdoos (B/H/D) mm	1233
Afmetingen Verpakkingsdoos (B/H/D) mm	704
Afmetingen Verpakkingsdoos (B/H/D) mm	62
Gewicht zonder standaard (kg)	13
Transportgewicht (Kg)	20
Haze Level [%]	Pro 25
HDMI	0
[AVSpecificationConnectivityOutputAudio35MmJack]	1
Audio/Koptelefoon Aansluiting 3,5 mm	1

Display

Beelddiagonaal (inches / cm)	55
Beelddiagonaal (inches / cm)	139

Mechanisch

Grootte Omlijsting (L/R) mm	10
Grootte Omlijsting (U) mm	10
Panel Technologie	IPS with Direct LED backlights
Eigen resolutie (aantal pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technologie	LED
Helderheid (cd/m2)	450
Contrast Ratio	1200:1
Reactietijd (grijs naar grijs gem) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (8bit + FRC)
Bedrijfsspanning (ACV) / Frequentie (Hz)	100-240
Bedrijfsspanning (ACV) / Frequentie (Hz)	50-60
Stroomverbruik (W) (MAX)	120
Werkende Temperatuur (oC)	0 to 40
Storage Temperature [°C]	-20 to 60
Storage Humidity [%]	10
Storage Humidity [%]	90
Energie Sterren	Ja
Liggend	Ja
Staand	Ja
Bevestiging (VESA/Aantal Punten/Pitch mm)	400 x 400 (FDMI)
Bevestiging (VESA/Aantal Punten/Pitch mm)	4
Bevestigingsbout Specificatie (grootte/Max Lengte)	M6
HDMI	3
Audio-aansluiting van 3,5 mm	1
RS232C IN	1
LAN-poort	1
USB	4

Omgevingsomstandigheden

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

© 2026 Sharp Display Solutions Europe GmbH. All rights reserved. All product names, company names, logos, trademarks, service marks and registered trademarks are the property of their respective owners. Design, features and specifications are subject to change without notice. Information is believed to be accurate at the time of publication. Errors and omissions excepted. Revision date: 09 July 2026. MultiSync ME552, 14/9/2026